

ELITE 1500 PRO

Line Interactive UPS



FEATURES

- Built-in AVR
- Wide input voltage range
- Compatible with Generator
- Intelligent Battery Management
- Overload protection
- Short circuit protection
- Overcharge protection.
- Battery deep discharge protection





ELITE 1500 PRO

Line Interactive UPS



SPECIFICATIONS

Capacity	1500VA	
INPUT		
Rating Voltage	220-240VAC	
Frequency	50/60Hz	
Current	7.2A Max	
Power Cord	Built-in Cable with fuse	
OUTPUT		
Waveform	Battery Mode (Simulated sine wave) AC Mode (Synchronize with Input)	
Power Factor	0.6	
Rating Voltage	220-240VAC	
Output Range	220VAC - 10% to + 10% (Battery Mode)	
Output sockets	4 x Universal - Battery Backup	
BATTERY		
Battery Type	Sealed lead acid, maintenance free	
Nominal voltage (VDC)	24VDC	
Number x Capacity (Ah) of battery	1 x 12V/8.2Ah	
Battery recharge time	6-8 hours to 90% after complete discharge	
Transfer time	Typical 4-8ms, 13ms Max	
Protection	Short circuit, Overcharge, Overload, Over discharge	
Communication Interface	NO	
GENERAL		
Physical Dimension (LxWxH)	353 x 149.3 x 162mm	
Enclosure/protection	IP20 (dustproof but not waterproof)	
Net Weight	8.7Kgs	
ENVIRONMENT		
Operating temperature	0-40 °C	
Noise Level (1M)	Less than 45dB	
Maximum relative humidity	0-90% (non - condensing)	